PATENT ABSTRACTS OF JAPAN

(11)Publication number:

2000-169867

 $-R^{\varepsilon} = (OR^{\varepsilon}), -OR^{\varepsilon}$

11

(43)Date of publication of application: 20.06.2000

(51)Int.CI.

C10M105/04 C10M107/34

(21)Application number: 10-349003

(71)Applicant : ASAHI GLASS CO LTD

(22)Date of filing:

08.12.1998

(72)Inventor: OTSUKA IWAHIRO

(54) MACHINE OIL COMPOSITION FOR REFRIGERATOR AND LUBRICATION USING THE **SAME**

(57)Abstract:

PROBLEM TO BE SOLVED: To obtain a machine oil composition for refrigerators that is increased in lubrication properties, sealing properties and refrigeration efficiency by using a specific refrigerant and R = [(OR') = OR']. a specific base oil. SOLUTION: This machine oil composition comprises (A)

a refrigerant mainly containing 1-8C hydrocarbons and (B) a polyether represented by formula I [R1 is an aromatic nucleus-bearing n-valent group; R2 is a 2-6C polymethylene, a group of polymelthylene of which one or more H atoms are substituted with a 1-20C alkyl, a group of polymethylene of which one or more H atoms are substituted with the group of formula II (R4 is

methylene, ethylene; R5 is a 2-6C polymethylene or the like; R6 is H, a 1-10C alkyl; (p) is 0-80); R3 is H, a 1-10C

alkyl; (n) is 1-6; (m) is a number that the average value of (m) x (n) becomes 3-80] (the dynamic viscosity is preferably 5-1,000 mm2/s). In a preferred embodiment, the weight ratio of the components A/B is 99/1-10/90,

and a lubricant composition containing the machine oil is used to lubricate a compression type refrigerator.

LEGAL STATUS

[Date of request for examination]

[Date of sending the examiner's decision of rejection]

[Kind of final disposal of application other than the examiner's decision of rejection or application converted registration]

[Date of final disposal for application]

[Patent number]

[Date of registration]

[Number of appeal against examiner's decision of rejection]

[Date of requesting appeal against examiner's decision of rejection]
[Date of extinction of right]

Copyright (C): 1998,2003 Japan Patent Office

(